

Letter No.1520...../

OFFICE OF THE STATE FIRE OFFICER-CUM-DIRECTOR, BIHAR, PATNA.

From,

Pankaj Sinha,
State Fire Officer,
Bihar, Patna.

To,

Ar. Achalesh Nandan,
Reg. No- AR14/15-16
Creative Designers,
35/C, Kankarbagh Housing Colony,
Near Auto Stand, Behind Urvashi Sales,
Patna-800 020.

Patna Dt. 28/09/2020

Sub :- The views regarding Proposed Residential Building of under 15 mtr. In height to be constructed at Mauza-Kumhrar, Dist-Patna.

Sir,

Please refer to your letter No.- 55/CD/2019, dt.-13/12/2019 through which this aforesaid plan has been sent to us for examination, which was examined by the Fire Service committee.

During examination of the plan it was found that a (G+4) (Total B/U Area-3251.62 Sqmtr.), Fully Proposed Residential Building shall be constructed on 30 feet wide road belongs to Smt. Prabhavati Devi, W/o-Sri Chandramaditya Singh & other, Plot No.-458,468, Khata No.-326,460, Tauzi No.-189,264, Thana No.-12, Thana No.-12, Mauza-Kumhrar, Dist-Patna.

We clear the plan after giving following advice/suggestions/recommendations based on NBC guideline, local building by laws & the local circumstances which must be followed by the concerned Architect/Developer/Land owner as the case may be.

i) Construction :

- The whole construction of the proposed building shall be carried out as per approved plan drawing conforming the relevant building rules of local Municipal Corporation as per Bihar building bye laws, 2014.
- The floor area exceeds 750 m² shall be suitably compartmented by separation walls up to ceiling level having at least two hours Fire resisting capacity.
- The interior finish decoration of the building shall be made low flame spread materials conforming I.S. specifications.
- Provision of ventilation at the crown of the central core-duct of the building shall be provided.
- Arrangements shall have to be made for sealing all the vertical ducts by the materials of adequate Fire resisting capacity.

ii) Open Space & Approach :

- The open space surrounding the building shall conform the relevant building rules as well as permit the accessibility and maneuverability of Fire appliance with turning facility.
- The approach roads shall be sufficiently strong to withstand the load of Fire Engine weighting up to 20 M.T.
- The width and height of the access gates into the premises shall not be less than 4.5 M and 5M respecting abutting the road.

iii) Stair Case :-

- The Staircase of the building shall be enclosed type. Entire construction shall be made of brick / R.C.C. type having Fire resisting capacity not less than 4 hours respectively marked in the plan.
- The Staircase of the building shall have permanent vents at the top equal to 5% of the cross sectional area of the staircase enclosures and openable sashes at each floor level equal to 15% of the said cross section are shall have to be provided in the external wall of the building.
- All the Staircase of the building shall be negotiable to each other in each floor without entering into any room and shall be extended up to respective terrace. The roof of the Stair wall shall be 1M above the surrounding roof area.
- The width of the Staircases and corridor and travel distance of different categories of occupancies shall have to confirm the relevant building rules.
- In case of two staircase, one must be on outer wall.

- f) Both staircase are not went down to basement floor, for approach to basement, there should be another staircase for approach.

iv) **LIFT :-**

- a) The walls of the Lift enclosure of the building shall be at least two hours Fire resisting type respectively marked in the plan with the event at top of area not less than 0.2 m².
- b) The lift of the building shall be designed at high speed "Fire Lift" and conspicuously indicated marked in the plan.
- c) In case of failure of normal electric supply, it shall automatically trip over to alternate supply. For apartment houses these change over of supply could be done through manually operated change over switch. Alternatively, the lift shall be so wired that in case of power failure, it comes down at the ground level land comes to stand still with door open.
- d) Arrangement shall be provided for extraction of smoke in all the lift shaft by incorporation smoke venting system designed to permit 30 Air changes per hour in case of Fire and shall be of such design as to operate on actuation of sprinkler or Fire Alarm. In case of failure of normal electric supply. It shall automatically trip to alternate supply.
- e) All other requirements shall conform the I.S. specification including the communication facility in the lift cars connecting with the Fire Control Room of the building.
- v) That active Fire protection system such as down comer system with landing valve and hose reel at each floor incorporated with 450 LPM pump at Terrace level, ISI marked Fire extinguishers as per I.S 2190/1992, F.R. check door, manual call alarm point, Fire safety luminescent sign & other Fire precautionary measures as mentioned in NBC be provided before occupancy.
- vi) That an underground water static tank of not less than 20,000 Ltrs. capacity with automatic refilling arrangements preferably on front side where Fire Brigade vehicles can reach easily & overhead water static tank of not less than 10,000 Ltrs. capacity each blocks should be made available before occupancy.
- vii) That the internal finishing shall be non-combustible or class - I surface spread of flame.
- viii) That electric cables must be shield at each floor with intumescent coating .
- ix) That Fire exit drill be carried out regularly at least twice in a year after occupation.
- x) That the building must be constructed on at least 20 feet wide road and it is responsibility of the concerned Architect to be ensure the road width because he is the passing authority.
- xi) That AMC should be given to a qualified firm or person for the maintenance of above recommended Fire equipments.
- xii) That the setback shall be checked by the Architect / Passing authority as per the established rule. If any thing wrong , the Architect / Passing authority shall be held responsible.
- xiii) It is hereby made clear that in case of any legal dispute arising in future, in which above recommendations have not been complied, the responsibility will fall entirely upon the Developers/ Architect/ Landowner as the case may be and not on the recommending Govt. authority (i.e. the office of the State Fire Officer, Bihar).
- xiv) It is hereby made also clear that this office (i.e. the office of the State Fire Officer-cum-Director, Bihar, Patna) is not responsible for any legal dispute of the land upon which the proposed building shall be constructed.
- xv) Set backs on all the sides adheres to the provisions for the fire safety as per bye laws. Whereas immediately beneath this area in the basement is adhering to the bye laws will be examined by the concerned Urban local bodies.

This shall be treated as provisional. On compliance of all the above Fire and Life Safety recommendations, this office shall be approached for necessary inspection and testing of the installation, Final approval in favor of the occupancy shall be issued on being satisfied with the tests and performances of safety aspects of installation of the building.

N.B. - Any deviation and changes the nature of use of the building in respect of the approved plan drawing without obtaining prior permission from this office, this provisional will be treated as cancelled.

The maps are being returned with sign and stamp .

Encl - As Above

Yours faithfully,

(Pankaj Sinha)
DIG HG & FS
Cum
State Fire Officer
Bihar, Patna

3We clear the plan after giving following advice/suggestions/recommendations based on NBC guideline, local building by laws & the local circumstances which must be followed by the concerned Architect/Developer/Land owner as the case may be.

i) Construction :

- a) The whole construction of the proposed building shall be carried out as per approved plan drawing conforming the relevant building rules of local Municipal Corporation as per Bihar building bye laws, 2014.
- b) The floor area exceeds 750 m² shall be suitably compartmented by separation walls up to ceiling level having at least two hours Fire resisting capacity.
- c) The interior finish decoration of the building shall be made low flame spread materials conforming I S specifications.
- d) Provision of ventilation at the crown of the central core-duct of the building shall be provided.
- e) Arrangements shall have to be made for sealing all the vertical ducts by the materials of adequate Fire resisting capacity.

ii) Open Space & Approach :

- a) The open space surrounding the building shall conform the relevant building rules as well as permit the accessibility and manoeuvrability of Fire appliance with turning facility.
- b) The approach roads shall be sufficiently strong to withstand the load of Fire Engine weighting up to 20 M.T.
- c) The width and height of the access gates into the premises shall not be less than 4.5 M and 5M respecting abutting the road.


iii) Stair Case :-


- a) The Staircase of the building shall be enclosed type. Entire construction shall be made of brick / R.C.C. type having Fire resisting capacity not less than 4 hours respectively marked in the plan.
- b) The Staircase of the building shall have permanent vents at the top equal to 5% of the cross sectional area of the staircase enclosures and openable sashes at each floor level equal to 15% of the said cross section are shall have to be provided in the external wall of the building.
- c) All the Staircase of the building shall be negotiable to each other in each floor without entering into any room and shall be extended up to respective terrace. The roof of the Stair wall shall be 1M above the surrounding roof area.
- d) The width of the Staircases and corridor and travel distance of different categories of occupancies shall have to confirm the relevant building rules.
- e) In case of two staircase, one must be on outer wall.
- f) Both staircase are not went down to basement floor, for approach to basement, there should be another staircase for approach.


iv) LIFT :-


- a) The walls of the Lift enclosure of the building shall be at least two hours Fire resisting type respectively marked in the plan with the event at top of area not less than 0.2 m².
- b) The lift of the building shall be designed at high speed "Fire Lift" and conspicuously indicated marked in the plan.
- c) In case of failure of normal electric supply, it shall automatically trip over to alternate supply. For apartment houses these change over of supply could be done through manually operated change over switch. Alternatively, the lift shall be so wired that in case of power failure, it comes down at the ground level and comes to stand still with door open.
- d) Arrangement shall be provided for extraction of smoke in all the lift shaft by incorporation smoke venting system designed to permit 30 Air changes per hour in case of Fire and shall be of such design as to operate on actuation of sprinkler or Fire Alarm. In case of failure of normal electric supply. It shall automatically trip to alternate supply.
- e) All other requirements shall conform the I.S. specification including the communication facility in the lift cars connecting with the Fire Control Room of the building.
- v) That active Fire protection system such as down comer system with landing valve and hose reel at each floor incorporated with 450 LPM pump at Terrace level, ISI marked Fire extinguishers as per I.S 2190/1992, F.R. check door, manual call alarm point, Fire safety luminescent sign & other Fire precautionary measures as mentioned in NBC be provided before occupancy.
- vii) That an underground water static tank of not less than 50,000 Ltrs. capacity with automatic refilling arrangements preferably on front side where Fire Brigade vehicles can reach easily & overhead water static tank of not less than 10,000 Ltrs. capacity each blocks should be made available before occupancy.
- viii) That the internal finishing shall be non-combustible or class - I surface spread of flame.
- ix) That electric cables must be shield at each floor with in tumescent coating.
- x) That Fire exit drill be carried out regularly at least twice in a year after occupation.
- xi) That the building must be constructed on at least 20 feet wide road and it is responsibility of the concerned Architect to be ensure the road width because he is the passing authority.
- xii) That AMC should be given to a qualified firm or person for the maintenance of above recommended Fire equipments.
- xiii) That the setback shall be checked by the Architect / Passing authority as per the established rule. If anything wrong, the Architect / Passing authority shall be held responsible.
- xiv) It is hereby made clear that in case of any legal dispute arising in future, in which above recommendations have not been complied, the responsibility will fall entirely upon the Developers/ Architect/ Landowner as the case may be and not on the recommending Govt. authority (i.e. the office of the State Fire Office, Bihar).
- xv) It is hereby made also clear that this office (i.e. the office of the State Fire Officer-cum-Director, Bihar, Patna) is not responsible for any legal dispute of the land upon which the proposed building shall be constructed.
- xvi) Set backs on all the sides adheres to the provisions for the fire safety as per bye laws. Whereas immediately beneath this area in the basement is adhering to the bye laws will be examined by the concerned Urban local bodies.

This shall be treated as provisional. On compliance of all the above Fire and Life Safety recommendations, this office shall be approached for necessary inspection and testing of the installation, Final approval in favor of the occupancy shall be issued on being satisfied with the tests and performances of safety aspects of installation of the building.


DIG HG & FS
Cum
State Fire Officer
Bihar, Patna

<div>INDIAN INCOME TAX RETURN ACKNOWLEDGEMENT</div> <div>[Where the data of the Return of Income in Form ITR-1 (SAHAJ), ITR-2, ITR-3, ITR- 4(SUGAM), ITR-5, ITR-6, ITR-7 filed and verified] (Please see Rule 12 of the Income-tax Rules, 1962)</div>			Assessment Year 2022-23	
PAN	AAACK9902G			
Name	KUMAR BUILDCON PVT LTD			
Address	201 N P CENTRE , NEW DAK BUNGLOW ROAD , PHULWARI , PATNA , 05-Bihar , 91-INDIA , 800001			
Status	Pvt Company	Form Number	ITR-6	
Filed u/s	139(1)-On or before due date	e-Filing Acknowledgement Number	746039871221022	
Taxable Income and Tax details	Current Year business loss, if any	1	0	
	Total Income		7,90,86,580	
	Book Profit under MAT, where applicable	2	8,20,94,726	
	Adjusted Total Income under AMT, where applicable	3	0	
	Net tax payable	4	2,20,01,886	
	Interest and Fee Payable	5	3,78,609	
	Total tax, interest and Fee payable	6	2,23,80,495	
	Taxes Paid	7	2,23,80,500	
	(+) Tax Payable / (-) Refundable (6-7)	8	(-) 10	
Accreted Income & Tax Details	Accreted Income as per section 115TD	9	0	
	Additional Tax payable u/s 115TD	10	0	
	Interest payable u/s 115TE	11	0	
	Additional Tax and interest payable	12	0	
	Tax and interest paid	13	0	
	(+) Tax Payable / (-) Refundable (12-13)	14	0	
This return has been digitally signed by KUMAR BUILDCON PVT LTD in the capacity of Director having PAN AFPPK0555A from IP address 182.69.242.115 on 22-Oct-2022 DSC SI.No & Issuer 91373482628044 & 91373482628044CN=Verasys CA 2014,OU=Certifying Authority,O=Verasys Technologies Pvt Ltd.,C=IN				
System Generated Barcode/QR code	<div> AAACK9902G06746039871221022a3c6198b25a68eab118ead80d00704948f0d623b</div>			
DO NOT SEND THIS ACKNOWLEDGEMENT TO CPC, BENGALURU				

INDIAN INCOME TAX RETURN ACKNOWLEDGEMENT				Assessment Year 2023-24
[Where the data of the Return of Income in Form ITR-1(SAHAJ), ITR-2, ITR-3, ITR-4(SUGAM), ITR-5, ITR-6, ITR-7 filed and verified] (Please see Rule 12 of the Income-tax Rules, 1962)				
PAN	AAACK9902G			
Name	KUMAR BUILDCON PVT LTD			
Address	201 N P CENTRE , NEW DAK BUNGLOW ROAD, PHULWARI , PATNA , 05-Bihar, 91-INDIA, 800001			
Status	7-Private company	Form Number	ITR-6	
Filed u/s	139(1)-On or before due date	e-Filing Acknowledgement Number	384028311041023	
Taxable Income and Tax Details	Current Year business loss, if any	1	0	
	Total Income	2	6,31,97,890	
	Book Profit under MAT, where applicable	3	7,01,80,613	
	Adjusted Total Income under AMT, where applicable	4	0	
	Net tax payable	5	1,75,81,652	
	Interest and Fee Payable	6	0	
	Total tax, interest and Fee payable	7	1,75,81,652	
	Taxes Paid	8	2,54,53,322	
	(+) Tax Payable /(-) Refundable (7-8)	9	(-) 78,71,670	
Accreted Income and Tax Detail	Accreted Income as per section 115TD	10	0	
	Additional Tax payable u/s 115TD	11	0	
	Interest payable u/s 115TE	12	0	
	Additional Tax and interest payable	13	0	
	Tax and interest paid	14	0	
	(+) Tax Payable /(-) Refundable (13-14)	15	0	
This return has been digitally signed by <u>PRAKASH KUMAR</u> in the capacity of <u>Director</u> having PAN <u>AFPPK0555A</u> from IP address <u>202.142.85.234</u> on <u>04-Oct-2023 13:38:34</u> at <u>PATNA</u> (Place) DSC SI.No & Issuer <u>4713925</u> & <u>91373482628044CN=Verasys CA 2014,OU=Certifying Authority,O=Verasys Technologies Pvt Ltd.,C=IN</u>				
System Generated Barcode/QR Code	 AAACK9902G06384028311041023d96dbf68f9b8ba8f6547f7220ddb12a47c5a8b0c			
<u>DO NOT SEND THIS ACKNOWLEDGEMENT TO CPC, BENGALURU</u>				

INDIAN INCOME TAX RETURN ACKNOWLEDGEMENT [Where the data of the Return of Income in Form ITR-1(SAHAJ), ITR-2, ITR-3, ITR-4(SUGAM), ITR-5, ITR-6, ITR-7 filed and verified] (Please see Rule 12 of the Income-tax Rules, 1962)				Assessment Year 2024-25			
PAN		AAACK9902G					
Name		KUMAR BUILDCON PVT LTD					
Address		201 N P CENTRE , NEW DAK BUNGLOW ROAD, PHULWARI , PATNA , 05-Bihar, 91-INDIA, 800001					
Status		7-Private company		Form Number		ITR-6	
Filed u/s		139(1)-On or before due date		e-Filing Acknowledgement Number		702964481141124	
Taxable Income and Tax Details	Current Year business loss, if any			1	0		
	Total Income			2	4,71,05,450		
	Book Profit under MAT, where applicable			3	6,57,12,265		
	Adjusted Total Income under AMT, where applicable			4	0		
	Net tax payable			5	1,31,04,735		
	Interest and Fee Payable			6	0		
	Total tax, interest and Fee payable			7	1,31,04,735		
	Taxes Paid			8	1,50,61,708		
	(+) Tax Payable /(-) Refundable (7-8)			9	(-) 19,56,970		
Accreted Income and Tax Detail	Accreted Income as per section 115TD			10	0		
	Additional Tax payable u/s 115TD			11	0		
	Interest payable u/s 115TE			12	0		
	Additional Tax and interest payable			13	0		
	Tax and interest paid			14	0		
	(+) Tax Payable /(-) Refundable (13-14)			15	0		
This return has been digitally signed by <u>PRAKASH KUMAR</u> in the capacity of <u>Director</u> having PAN <u>AFPPK0555A</u> from IP address <u>110.226.36.31</u> on <u>14-Nov-2024 17:37:49</u> at <u>PATNA</u> (Place) DSC SI.No & Issuer <u>4713925</u> & <u>130231122160982437166926296081952592136CN=ProDigiSign Sub CA DSC 2022,OU=Certifying Authority,O=Professional DigiSign Pvt. Ltd.,C=IN</u>							
System Generated Barcode/QR Code		 AAACK9902G0670296448114112464e61794c1b62944e4889565c27b486953916765					
DO NOT SEND THIS ACKNOWLEDGEMENT TO CPC, BENGALURU							