PLAN OF THE PROPOSED BUILDING
(APARTMENT) TO BE CONSTRUCTED BY
SRI RAVI PRASAD SAHU
S/O LATE MANGAL PRASAD SAHU,
SRI AKHILESH SAHU
S/O. SRI RAVI PRASAD SAHU
SRI ANIMESH SAHU
S/O SRI RAVI PRASAD SAHU
AND SRI ARVIND SAHU
S/O LATE PRABHAKAR PRASAD SAHU
TO BE DEVELOPED BY
M/S ASHA REALTY DEVELOPERS PRIVATE LIMITED
MANAGING DIRECTOR MRS MADHURI GUPTA
W/O SRI ASHWINI KUMAR GUPTA
ON KHATA NO :- 89
KHESRA NOS :- 163
AT- MOHALLA :- SAHU ROAD
WARD NO:- 27
P.S. :- KOTWALI
DISTT:- MUZAFFARPUR
SCALE 1:150

AREA STATEMENT

PLOT AREA =	1018.32 SQM
GROUND FLOOR AREA =	26.3 SQM
(INC LIFT AREA)	
FIRST FLOOR AREA =	325.9 SQM
2ND FLOOR AREA =	325.9 SQM
3RD FLOOR AREA =	325.9 SQM
4TH FLOOR AREA =	325.9 SQM
5TH FLOOR AREA =	325.9 SQM
6TH FLOOR AREA =	325.9 SQM
MACHINE ROOM AREA =	9.8L SQM
TOTAL =	1990.71 SQM
FAR = 1.954	

APPROVED BY

GROUND FLOOR PLAN

TYPICAL FLOOR PLAN
FIRST TO SIXTH FLOOR PLAN

SECTION ON A-A

SECTION ON B-B

SITE PLAN
SCALE 1: 600

LOCATION PLAN

SIDE ELEVATION

FRONT ELEVATION

DETAIL OF SEPTIC TANK & SOAK PIT

ELEVATION
PLAN
DETAILS OFBOUNDARY WALL

DET. OF RECHARGEABLE BORE WELL

SECTION AT A-A

FIRE LEGEND

1. HYDRANT LAYOUT VALVE WET
2. HOSE REEL
3. SIAMESE CONNECTION FOR FIRE BRIDGE USE IS 908: WET RISING SYSTEM
4. MANUAL CALL POINT
5. SPRICATER PAIPE
6. AUDIABLE & WARNING DEVICES
7. FIRE EXASTINGUISHER
8. OVER HEAD WATER TANK CAP 4.0M3T 100 LUMPHR
9. UNDER GROUND WATER TANK WITH AUTOMATIC SETTLING ARRANGEMENT
10 F.R. DOOR
11. GROUND HYDRANT
12. ILLUMINATED EXIT DIRECTIONAL SIGN

WATER TANK CALCULATION

TOTAL BUILT UP AREA =1990.71 SQM
NO OF FLATS = 18
6 PERSON PER FLAT=18X6= 108 PERSONS
135LTR/PERSON=135X108=14580 LTR.
PROVIDE WATER TANK FOR 3.675 CUMTR
SIZE :- 1.5X 1.5 X1.3 +.3 FB = 3.675 CUMTR.

SEPTIC TANK CALCULATION

TOTAL BUILT UP AREA =1990.71 SQM
NO OF FLATS = 18
6 PERSON PER FLAT=18X6= 108 PERSONS
REQU. =108X0.085CUMTR=9.18 CUMTR.
PROVIDE SEPTIC TANK FOR 14.4 CUMTR
SIZE = 4 X2.00X1.8 +.3 FB =14.4 CUL.TR.

PARKING CALCULATION

TOTAL BUILT UP AREA = 1990.71 SQM
NO OF FLATS = 18
HENCE PROVIDING 18 PARKING SPACE
ONE CAR PARKING = 20 SQM =18X20 = 360 SQM
TWO WHEELER PARKING REQ. 1.5 SQMPVEHICLE
=1.5X20 =30 SQM
TOTAL REQUIRED PARKING =360+30=390 SQM
PROVIDED PARKING IN STILT FLOOR =299.6 SQM
PROVIDED PARKING IN OPEN SPACE =90.4 SQM
TOTAL PROVIDING PARKING AREA =390 SQM

SPECIFICATIONS

1. FOUNDATION	RCC
2. FLOOR SLAB	150 THICK RCC SLAB WITH 1:4:8 CEM. SAND & STONE JELLY CONCRETE
3. ROOF STRUCTURE	150 THICK RCC SLAB WITH 1:4:8 CEMENT CONCRETE
4. FLOORING	20MM THICK TILES FLOORING OVER 30MM CEMENT PLASTER
5. PLASTER	20 MM THICK CEMENT PLASTER WITH 1:4 CEMENT MORTAR
6. DOORS	32MM THICK FLUSH DOOR WITH ALUMINIUM FRAME
7. WINDOWS	WOOD FRAMED SHUTTERS WITH GLASS PANES
	ALUMINIUM SLIDING WINDOWS
	ALUMINIUM VENTILATORS
8. RAILING	TWO COATS CEMENT PAINT WASHING OVER PUTTY OVER 1 COAT OF CEMENT PRIMER OVER 1 COAT OF RED OXIDE
9. SANITARY FITTINGS	ALL SANITARY FITTINGS SHALL BE OF BEST QUALITY
	1 NOS OF OVERHEAD WATER TANK
	1 NOS OF UNDERGROUND WATER TANK WITH SUMP PUMP
	1 NOS OF SEPTIC TANK WITH SOAK PIT
	1 NOS OF LIFT OF 6 PASSENGER CAPACITY

TYPICAL RIDGE BEAM

SCHEDULE OF OPENINGS

TYPE	SIZE	DESCRIPTION
D1	1.01X2.17	FULLY
D2	0.91X2.17	PANNELED
D3	0.76X2.17	DOOR
D4	1.07X 2.13	
W1	0.9 X 1.07	FULLY GLAZED
V	0.61X0.91	WINDOW

DRAWN BY

M. K. ALI

Ravi Prasad Sahu
Akhilesh Sahu
Animesh Sahu
Arvind Sahu

APPLICANTS SIGNATURE

DESIGNED BY

STATE FINANCE OFFICER
BIHAR, PATNA

ARUN KUMAR
B.E., M. Tech (Civil)
Valuer, Estimator, Designer
M.R.D.A. LIC No-C-86/2009